



PEKA FORTE

Vollauszug für Holzkonstruktionen
Extension complète pour constructions de caisses en bois
Full-extension runner for wooden cabinets








Art.Nr.





380
100.1368.xx
430
100.1369.xx
480
100.1370.xx
530
100.1371.xx
580
100.1372.xx
630
100.1373.xx
680
100.1374.xx
780
100.1375.xx
880
100.1376.xx
980
100.1377.xx
1080
100.1378.xx



+41 41 919 94 04





1x 	1x 	1x 	1x Version A 	1x Version B 
---	---	---	---	---

Option	Option
1x  100.1380.xx	1x  100.1379.xx




EB	max. 600	max. 800
----	-------------	-------------




Typ/Type	LT	X	100.1379.xx
380	385	352	✗
430	435	402	✓
480	485	452	
530	535	502	
580	585	552	
630	635	602	
680	685	652	
780	785	752	
880	885	852	
980	985	952	
1080	1085	1052	






DE Möbelboden und Sockel müssen für 170/340 kg ausreichend verstärkt und tragfähig sein!
FR Le fond de meuble et le socle doivent être suffisamment renforcés et porteurs pour 170 / 340 kg !
EN The furniture base and plinth must be sufficiently reinforced and load-bearing for 170 / 340 kg!





Technical drawing of a corner joint showing dimensions: 65, min. 124, and two sets of double lines indicating specific features.








Typ/Type	A
380	300
430	350
480	400
530	450
580	500
630	550
680	600
780	700
880	800
980	900
1080	1000







Option Softclose




Typ/Type
480, 530, 580,
630, 780
880, 980, 1080




Typ/Type
430









1x Version A






C







Typ/Type	C
380	280
430	330
480	380
530	430
580	480
630	530
680	580
780	680
880	780
980	880
1080	980








Typ/Type	d	e	f	g
380	150	50	100	-
430		100	100	
480		150	100	
530		200	100	
580		100	150	
630	200	150	150	100
680		200	150	
780		200	200	
880		300	200	
980		400	200	
1080		500	200	





5

1





Rückwand- und Frontausschnitt
Découpe du panneau arrière et de la façade
Back wall and front cut-out



Version A (Standard)
Y = 16 mm

2x



2x



2x



8x




6x




Version B
Y = 16-30
Durchgehend verschraubt
Vissé traversante
Bolted through

4x



4x



4x



12x







2x





6x




16





Typ/Type	A
380	300
430	350
480	400
530	450
580	500
630	550
680	600
780	700
880	800
980	900
1080	1000






Option Softclose




Typ/Type
480, 530, 580,
630, 780
880, 980, 1080






Typ/Type
430










Option






100.1380.xx







Typ/Type	C
380	280
430	330
480	380
530	430
580	480
630	530
680	580
780	680
880	780
980	880
1080	980










Typ/Type	d	e	f	g
380	150	50	100	-
430		100	100	
480		150	100	
530		200	100	
580		100	150	
630	200	150	150	100
680		200	150	
780		200	200	
880		300	200	
980		400	200	
1080		500	200	



5

2












Version B

Y= 16-30

Durchgehend verschraubt

Vissé traversante

Bolted through



Typ Type	LT	X	A	C	100.1379.xx
380	385	352	300	280	—
430	435	402	350	330	✓
480	485	452	400	380	
530	535	502	450	430	
580	585	552	500	480	
630	635	602	550	530	
680	685	652	600	580	
780	785	752	700	680	
880	885	852	800	780	
980	985	952	900	880	
1080	1085	1052	1000	980	